

TEVESI®

ABSORBI PRO



DESCRIPTION:

Tevesi® Absorbi Pro sets itself apart in our product range with its innovative use of viscose cleaning cloth material, providing superior absorption—up to 7 to 10 times its weight—compared to traditional polyester made from recycled PET bottles. This durable yet lightweight protective solution delivers the same high-quality performance you've come to expect, now with added efficiency.

The viscose top layer ensures enhanced liquid absorption, while the self-adhesive PE-film underlayer secures it in place, eliminating the need for tape. This makes Tevesi® Absorbi Pro perfect for protecting floors during painting, plastering, moving, or construction projects.

With an absorption capacity ranging from 1.015 to 1.45 liters per square meter, Tevesi® Absorbi Pro offers optimal protection and ease of use in any environment.

APPLICATION

- LVT
- Tile
- Countertops
- Stairs
- Other surfaces

FEATURES

- Self-adhesive
- Highly absorbent
- Shock-absorbing
- Moisture resistant
- Reusable
- Anti-slip



TECHNICAL DATA

Appearance	TL.014	-
Width	TL.013	100 cm
Weight	TS EN 29073-1	145 g/m ²
Thickness	TS EN 29073-2	1,5 mm
Tensile strength (CD)	TS EN 29073-3	N/5cm 100
Tensile elongation (CD)	TS EN 29073-3	100% (+/- 10%)
Tensile strength (MD)	TS EN 29073-3	N/5cm 100
Tensile elongation (MD)	TS EN 29073-3	80% (+/-20%)
Water vapour permeability	ASTM E398	N.A.
Tearing strength (CD)	TS EN ISO 90732-4	1 kg
Tearing strength (MD)	TS EN ISO 90732-4	2 kg
Peeling at 180	D41 1015	

MATERIAL

- Material - Viscose cleaning cloth
- Adhesive - Water-based acrylic
- Color - Yellow
- Laminated - Laminated with a film