

PERFECT COVER® STANDARD



DESCRIPTION:

Perfect Cover® Standard has a liquid-tight top layer and a self-adhesive underside, which is suitable for all hard and smooth floors such as: laminate, PVC, tiles, plastic floors and stairs. Ideal for painting, plastering, moving and building.

Application: The substrate must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary tests. Lay the rolls with an overlap of approximately 4 inches (10 cm) and press firmly. Processing temperature should be between 41°F and 104°F (5-40 °C). Not suitable for recently laid concrete. The underfloor heating must be switched off.

APPLICATION

- LVT
- Tile
- Countertops
- Stairs
- Other surfaces

FEATURES

- Self-adhesive
- Shock-absorbing
- Moisture resistant
- Reusable
- Anti-slip



TECHNICAL DATA

Appearance	TL.014	-
Width	TL.013	39.37 in (100 cm)
Weight	TS EN 29073-1	0.476 oz/sq. ft. (160 g/m ²)
Thickness	TS EN 29073-2	59.06 mils (1.5 mm)
Tensile strength (CD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (CD)	TS EN 29073-3	100% (+/- 10%)
Tensile strength (MD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (MD)	TS EN 29073-3	80% (+/-20%)
Water vapour permeability	ASTM E398	N.A.
Tearing strength (CD)	TS EN ISO 90732-4	2.205 lb (1 kg)
Tearing strength (MD)	TS EN ISO 90732-4	4.41 lb (2 kg)
Peeling at 180	D41 1015	

MATERIAL

- Material - Non-woven made of 100% PES fibers
- Adhesive - Water-based acrylic
- Color - White
- Laminated - Laminated with a non-breathable film

