


PERFECT COVER® VAPOR PRO



DESCRIPTION:

Perfect Cover Vapor Pro is an extremely breathable, self-adhesive floor protection membrane designed for, among others, newly laid floors. This membrane allows moisture to escape from the bottom while remaining moisture-proof from the top. It boasts the highest vapor permeability, allowing 73.8 oz/yd²/day (2500 g/m²/24 h). Perfect Cover Vapor Pro features a bottom layer of non-slip, lightly adhesive fiber fleece with a special membrane. This ensures that the curing process of new floors is not adversely affected.

Application: The substrate must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary tests. Lay the rolls with an overlap of approximately 4 inches (10 cm) and press firmly. Processing temperature should be between 41°F and 104°F (5-40 °C). Not suitable for recently laid concrete. The underfloor heating must be switched off.

APPLICATION

- Covering Natural Stone
- Covering cement-bonded poured floors
- Covering concrete floors
- Covering parquet
- Covering newly laid floors
- Covering poured floors

FEATURES

- Self-adhesive
- Ultra Breathable
- Shock-absorbing
- Moisture resistant
- Reusable
- Anti-slip



TECHNICAL DATA

Appearance	TL.014	-
Width	TL.013	39.37 in (100 cm)
Weight	TS EN 29073-1	0.476 oz/sq. ft. (160 g/m ²)
Thickness	TS EN 29073-2	83.5 mils (2.12 mm)
Tensile strength (CD)	TS EN 29073-3	lbf/in 14.2 (N/5cm 124)
Tensile elongation (CD)	TS EN 29073-3	% 50
Tensile strength (MD)	TS EN 29073-3	lbf/in 15 (N/5cm 131)
Tensile elongation (MD)	TS EN 29073-3	% 37
Water vapour permeability	DIN 52615	73.8 oz/yd ² /day (2500 g/m ² /24 h)
Tearing strength (CD)	TS EN ISO 90732-4	2.205 lb (1 kg)
Tearing strength (MD)	TS EN ISO 90732-4	2.205 lb (1 kg)
Peeling at 180	D41 1015	4.41 lb (2 kg)

MATERIAL

- Material - Non-woven made of 100% PES fibers
- Adhesive - Water-based acrylic
- Color - Blue
- Laminated - Laminated with an impermeable, breathable nonwoven

