

# PERFECT COVER®

## BREATHABLE



### DESCRIPTION:

Perfect Cover Breathable is a highly breathable, self-adhesive floor protection membrane designed for newly laid floors. This membrane allows moisture to escape from the bottom while remaining moisture-proof from the top. It boasts the highest vapor permeability, allowing 0.0295 gal/ft<sup>2</sup>/day (1.2L/m<sup>2</sup>/24 h). Consisting of multiple layers, Perfect Cover Breathable features a bottom layer of non-slip, lightly adhesive fiber fleece with a special membrane. This ensures that the curing process of new floors is not adversely affected.

Additionally, the bottom layer is equipped with an anti-slip coating that is resistant to moisture, making it suitable for use on newly laid floors without any issues. Application: The substrate must remain dry, clean, dust-free, and free from chemical agents. It is advisable to conduct preliminary tests. Lay the rolls with an overlap of approximately 4 inches (10 cm) and press firmly. Processing temperature should be between 41°F and 104°F (5-40 °C). Not suitable for recently laid concrete. The underfloor heating must be switched off.

### APPLICATION

- Covering Natural Stone
- Covering cement-bonded poured floors
- Covering concrete floors
- Covering parquet
- Covering newly laid floors
- Covering poured floors



### FEATURES

- Self-adhesive
- Highly Breathable
- Shock-absorbing
- Moisture resistant
- Reusable
- Anti-slip

### TECHNICAL DATA

Appearance	TL.014	-
Width	TL.013	39.37 in (100 cm)
Weight	TS EN 29073-1	0.59 oz/sq. ft. (180 g/m <sup>2</sup> )
Thickness	TS EN 29073-2	59.06 mils (1.5 mm)
Tensile strength (CD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (CD)	TS EN 29073-3	% 100
Tensile strength (MD)	TS EN 29073-3	lbf/in 11.42 (N/5cm 100)
Tensile elongation (MD)	TS EN 29073-3	% 80
Water vapour permeability	ASTM E398	0.0295 gal/ft <sup>2</sup> /day (1.2L/m <sup>2</sup> /24 h)
Tearing strength (CD)	TS EN ISO 90732-4	2.205 lb (1 kg)
Tearing strength (MD)	TS EN ISO 90732-4	2.205 lb (1 kg)
Peeling at 180	D41 1015	4.41 lb (2 kg)

### MATERIAL

- Material - Non-woven made of 100% PES fibers
- Adhesive - Water-based acrylic
- Color - White/blue
- Laminated - Laminated with an impermeable, breathable nonwoven

